Nexans MOBIWAY[™] POP

Nexans MOBIWAY POP, disruptive solution for residencial and commercial installers

Open! Insert! Unwind!

DESCRIPTION

An innovative system to easily transport and unwind wires: Nexans <u>MOBIWAY™POP</u>.

Nexans MOBIWAY[™]POP Kit consists of :

- A new format spool, in lengths of 100m
- An innovative tool to insert and unwind MOBIWAY[™]POP spool.

The benefits:

- · Reduce wiring time
- · Optimizes the installation process and labor
- Facilitates transportation
- Enhances safety
- Eliminates the spiral effect
- Requires 30% less storage space
- Reduces environmental impact

Nexans <u>MOBIWAY</u>[™]<u>POP</u>its a new solution to **easyly transport and undwind wires** thanks to its disruptive packgagin unit and a practical tool. It combines a new 100 meter spool format and a reusable tool that has a lockable tab, a guidance system, a guide lock rewind system and a grab handle.

Transport and unwind your wires in few steps:

- Open the lockable tabs.
- · Insert the spools.
- Lock the lockable tabs
- Put the wires together
- Pass trough the guidance system
- Unwind the wires

When the spool is empty, simply unlock the **<u>MOBIWAY™ POP</u>** tabs and **insert** a new **<u>MOBIWAY™ POP</u>** spool.

Made in France.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans. Generated 11/10/23 www.nexans.co Page 1 / 4





CHARACTERISTICS

Dimensional characteristics	
Approximate net weight	2.5 kg
Height	180 mm
Width	260 mm

PRODUCT LIST

Nexans Ref.	Country Ref.	Name
4 70528	-	Nexans MOBIWAY™ POP
		📞 = Make to order, 🛔 = In stock,

MOBIWAY[™] POP MATERIALS LIST

Part Name - Material - Detail

Chassis- ABS Plastic - Acrylonitrile butadiene styrene Tabs - ABS Plastic - Acrylonitrile butadiene styrene Rewind Handle - POM Plastic - Polyformaldehyde Non-slip Feet - TPU Plastic - Thermoplastic Polyurethane Bearings - POM Plastic - Polyformaldehyde Wire Guide - ABS Plasti - Acrylonitrile butadiene styrene Spacer Tubes - Aluminum Strap Plates - Stainless Steel Transport Handle - Wood Handle Straps - Synthetic Fabric Carry Strap - Synthetic Fabric

MOBIWAY[™] MOB HEAVY DUTY

Mobiway[™] POP is reusable and resistant to any test, thanks to its 100% ABS material.

It also comes with a 3-year warranty.

MOBIWAY™ POP RECOMMENDATIONS AND MAINTENANCE

- Mobiway[™] POPis waterproof; however, it is recommended to store it in a dry place.
- Mobiway[™] POPis dust-resistant; nonetheless, it is advisable to clean it regularly using a dry cloth.
- If necessary, **Mobiway™ POP** can be washed using only water and soap. The use of any other chemicals such as chlorides, acetones, degreasers, etc., accelerates the aging of the device.
- The bearing mechanisms of **Mobiway™ POP** do not require any type of lubrication.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans. Generated 11/10/23 www.nexans.co Page 2 / 4



Nexans MOBIWAY[™] POP

MOBIWAY™ POP USE INSTRUCTIONS

A. PARA INICIAR LA INSTALACIÓN



B. AL FINALIZAR LA INSTALACIÓN



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans. Generated 11/10/23 www.nexans.co Page 3 / 4



Nexans MOBIWAY[™] POP

MOBIWAY™ POP DIMENSIONS



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans. Generated 11/10/23 www.nexans.co Page 4 / 4

